



**PRODUCT: RIGID POLYURETHANE FOAM
AIRMETIC SOYA/ HEATLOK SOYA 0240-0**

MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT & COMPANY INFORMATION

MANUFACTURER OF CHEMICAL COMPONENTS

Demilec Inc.
870 Curé Boivin
Boisbriand, QC
Canada
J7G 2A7
Téléphone 1-866-437-0223
Fax (450) 437-2338
E-mail: demilec@demilec.com

PRODUCT

Trade name: RIGID POLYURETHANE FOAM
AIRMETIC SOYA/HEATLOK SOYA

Chemical name: RIGID URETHANE FOAM PLASTIC
Chemical family: URETHANE
Product use: INSULATION

EMERGENCY TELEPHONE: CANUTEC (613) 996-6666

SECTION 2: HAZARDS IDENTIFICATION

Physical State / Color/
Odor Rigid cellular plastic / Green / Neutral

Emergency Overview / Warning

Routes of Entry	Skin contact, inhalation (only if dust is created during cutting)
Eye Contact with dust	May cause mechanical irritation to eyes.
Skin Contact with dust	May cause mechanical irritation to skin.
Dust Inhalation	May cause mechanical irritation to respiratory system.
Dust Ingestion	May cause choking if swallowed.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS #	%
Urethane Plastics	9009-54-5	90 – 100
Blowing agent blend	Secret	1 – 5

SECTION 4: FIRST AID MEASURES

Eye Contact	Flush eyes with running water for a minimum of 15 minutes.
Skin Contact	Wash with soap and water thoroughly.
Inhalation	Remove to fresh air if effects occur. If not breathing, give artificial respiration. If breathing is difficult, assist with oxygen. Consult physician.
Ingestion	No adverse effects anticipated by this route.

SECTION 5: FIRE FIGHTING MEASURES

Auto-Ignition Temperature	343-427°C (650-800°F)
---------------------------	-----------------------



**PRODUCT: RIGID POLYURETHANE FOAM
AIRMETIC SOYA/ HEATLOK SOYA 0240-0**

Suitable Extinguishing Media	Use water, dry chemical, carbon dioxide or chemical foam.
Hazardous Decomposition	Under fire conditions, carbon monoxide, carbon dioxide, hydrogen halides, phosphorous oxide and possible traces of hydrogen cyanide and nitrogen oxides.
Special Fire Fighting Procedures	Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus with positive pressure. Material supports combustion.
Precautions	<p>Rigid polyurethane foam, like other organic materials such as paper, wood and cotton, can present fire risks in some applications when exposed to ignition sources. Once ignited, fires can burn rapidly and produce rapid flame spread, quick flashover, toxic or flammable gases, dense smoke and intense heat. In no event should the polyurethane foam remain exposed or unprotected. Make no application of foam to interior wall and ceilings or other space enclosures without prompt and subsequent application of approved thermal barriers. No welding or flame cutting until proper surface protection has been provided.</p> <p>1) Respect 2 inches maximum thickness per pass. Make no application of foam with total successive passes thickness greater than 4 inches, it may cause spontaneous combustion of the foam to occur, often hours after the foam was applied. For application greater than 4 inches, allowed first 4 inches thick successive passes of installed foam to cool down before applying any additional lift.</p> <p>2) Make no application of foam to interior wall and ceilings or other space enclosures without prompt and subsequent application of approved thermal barriers.</p> <p>3) Do no welding, flame cutting or having flame source until proper foam surface thermal protection has been provided.</p> <p>4) Avoid the confined storage of large urethane foam buns.</p>

SECTION 6: ACCIDENTAL RELEASE MEASURES

No information available. Refer to Section 13.

SECTION 7: HANDLING & STORAGE

General information	Keep away from open flame, electrical or mechanical sparks, electric heaters, high powered lights, flame sources and flammable liquids and gases. Protect all indoor bun and sheet storage areas with fusible sprinkles.
---------------------	--

SECTION 8: EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure Limit Values			
Ingredients	WEEL (AIHA) (TWA) – 8 hr	OSHA PEL (TWA) – 8 hr	RSST (TWA)
Urethane Plastics	N/A	N/A	N/A
Blowing agent blend	1 000 ppm	N/A	N/A
Eye Protection	Safety glasses during cutting.		
Skin Protection	Protective clothing to minimize skin exposure.		
Respiratory Protection	Dust mask during cutting.		
Ventilation	Use sufficient ventilation to keep exposure to dust at a minimum (below 5 mg/m ³ breathable)		



**PRODUCT: RIGID POLYURETHANE FOAM
AIRMETIC SOYA/ HEATLOK SOYA 0240-0**

	nuisance dust).
--	-----------------

SECTION 9: PHYSICAL & CHEMICAL PROPERTIES	
Appearance	Rigid cellular plastic
Odor	Neutral
Density	2,0 to 2,4 pcf
Melting Point	N/A, Thermoset.
Decomposition temperature	>121°C (>250°F)
Maximum Service Temperature	82°C (180°F)
Solubility in Water	None

SECTION 10: STABILITY & REACTIVITY	
Stability	This product is considered stable under normal conditions.
Incompatibility	None known
Hazardous Decomposition	Under fire conditions, carbon monoxide, carbon dioxide, hydrogen halides, phosphorous oxide and possible traces of hydrogen cyanide and nitrogen oxides.
Hazardous Polymerization	None
Corrosive Properties	None
Oxidizer Properties	None
Chemical Resistance	Stable in the presence of most solvents found in binders, bituminous materials, wood preservatives and sealers. Resistant to facers containing plasticizer, fuel, mineral oil, weak acids and weak bases. Resistant to fungi and microbes. UV rays cause a darkening of the foam surface and with time will degrade the surface.

SECTION 11: TOXICOLOGICAL INFORMATION	
Potential Acute Health Effects	
Eye Contact	May cause mechanical irritation to eyes.
Skin Contact	May cause mechanical irritation to skin.
Dust Inhalation	May cause mechanical irritation to respiratory system.
Dust Ingestion	May cause choking if swallowed.
Potential Chronic Health Effects	
Sensitization	Not known or reported.
Carcinogenic Effects	The components of this product are not listed by NTP, IARC or regulated as a carcinogen by OSHA.
Mutagenic Effects	No known significant effects or critical hazards.



**PRODUCT: RIGID POLYURETHANE FOAM
AIRMETIC SOYA/ HEATLOK SOYA 0240-0**

Reproductive Effects	No known significant effects or critical hazards.
Developmental Effects	No known significant effects or critical hazards.

SECTION 12: ECOLOGICAL INFORMATION

Aquatic Toxicity Data For Components Toxicity

Urethane Plastics	No data on product itself.
Blowing agent blend	Fishes, Brachydanio rerio, LC50, 96 h, > 200 mg/l Fishes, Pimephales promelas, NOEC, 30 days, ca. 38.2 mg/l Crustaceans, Daphnia magna, EC50, 48 h, >200 mg/l Algae, Selenastrum capricornutum, NOEC, 72 h, = 13.2 mg/l Algae, Selenastrum capricornutum, EC50, 72 h, > 114 mg/l Terrestrial plants, NOEC, growth, >=6 g/m3

SECTION 13: DISPOSAL CONSIDERATION

Waste Disposal Method	The generation of waste should be avoided or minimized whenever possible. Waste must be disposed of in compliance with federal, state, provincial and local environmental control regulations.
Demilec Inc. has no control over the management practices or manufacturing processes of parties handling or using this material.	

SECTION 14: TRANSPORTATION INFORMATION

Technical Shipping Name	SPRAY-APPLIED RIGID POLYURETHANE FOAM AIRMETIC SOYA/ HEATLOK SOYA 0240-0
Land Transport / DOT Classification	Non-regulated
Sea Transport / IMDG Classification	Non-regulated
Air Transport / ICAO / IATA Classification	Non-regulated
TDG Classification	Non-regulated

SECTION 15: REGULATORY INFORMATION

WHMIS	Non-regulated.
CEPA (DSL)	Non-regulated.
TSCA	Non-regulated.
RSST	This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

SECTION 16: OTHER INFORMATION

This product does not contain nor is it manufactured with ozone depleting substances.



**PRODUCT: RIGID POLYURETHANE FOAM
AIRMETIC SOYA/ HEATLOK SOYA 0240-0**

Notice:

The information herein is presented in good faith and believed to be accurate as of the effective date shown below. However, no warranty expressed or implied is given. Regulatory requirements are subject to change and may differ from one location to another; it is user's responsibility to ensure that its activities comply with country, provincial and local laws.

This product may present hazards and should be used with caution. While certain hazards are described in this publication, no guarantee is made that these are only hazards that exist. Hazards, toxicity and behavior of the products may differ when used with other materials and are dependent upon manufacturing circumstances or other processes. Such hazards, toxicity and behavior should be determined by the user and made known to handlers, processors and end users.

Prepared by	Demilec Inc.
Preparation Date	January, 2014
Current Issue Date	January, 2014